

Fluid-structure interaction assessment of blood flow hemodynamics and leaflet stress during mitral regurgitation

Adham Esfahani, Saeed; Hassani, Kamran; Espino, Daniel

DOI:

[10.1080/10255842.2018.1552683](https://doi.org/10.1080/10255842.2018.1552683)

License:

Other (please specify with Rights Statement)

Document Version

Peer reviewed version

Citation for published version (Harvard):

Adham Esfahani, S, Hassani, K & Espino, D 2018, 'Fluid-structure interaction assessment of blood flow hemodynamics and leaflet stress during mitral regurgitation', *Computer Methods in Biomechanics and Biomedical Engineering*. <https://doi.org/10.1080/10255842.2018.1552683>

[Link to publication on Research at Birmingham portal](#)

Publisher Rights Statement:

This is an Accepted Manuscript of an article published by Taylor & Francis in *Computer Methods in Biomechanics and Biomedical Engineering* on 31/12/2018, available online: <https://www.tandfonline.com/doi/full/10.1080/10255842.2018.1552683>

General rights

Unless a licence is specified above, all rights (including copyright and moral rights) in this document are retained by the authors and/or the copyright holders. The express permission of the copyright holder must be obtained for any use of this material other than for purposes permitted by law.

- Users may freely distribute the URL that is used to identify this publication.
- Users may download and/or print one copy of the publication from the University of Birmingham research portal for the purpose of private study or non-commercial research.
- User may use extracts from the document in line with the concept of 'fair dealing' under the Copyright, Designs and Patents Act 1988 (?)
- Users may not further distribute the material nor use it for the purposes of commercial gain.

Where a licence is displayed above, please note the terms and conditions of the licence govern your use of this document.

When citing, please reference the published version.

Take down policy

While the University of Birmingham exercises care and attention in making items available there are rare occasions when an item has been uploaded in error or has been deemed to be commercially or otherwise sensitive.

If you believe that this is the case for this document, please contact UBIRA@lists.bham.ac.uk providing details and we will remove access to the work immediately and investigate.

Fluid-Structure Interaction Assessment of Blood Flow Hemodynamics and Leaflet Stress During Mitral Regurgitation

Saeed Adham Esfahani¹, Kamran Hassani², and Daniel M.Espino³

¹ Mechanical Engineering Department, Majlesi Branch, Islamic Azad University, Isfahan, Iran.

² Department of Biomechanics, Science and Research Branch, Islamic Azad University, Tehran, Iran.

³ Department of Mechanical Engineering, University of Birmingham, Birmingham, UK

Abstract

The aim of this study is to simulate the Mitral Regurgitation (MR) disease progression from mild to severe intensity. A Fluid Structure Interaction (FSI) model was developed to extract the hemodynamic parameters of blood flow in mitral regurgitation (MR) during systole. A two-dimensional (2D) geometry of the mitral valve was built based on the data resulting from Magnetic Resonance Imaging (MRI) dimensional measurements. The leaflets were assumed to be elastic. Using COMSOL software, the hemodynamic parameters of blood flow including velocity, pressure, and Von Mises stress contours were obtained by moving arbitrary Lagrange-Euler mesh. The results were obtained for normal and MR cases. They showed the effects of the abnormal distance between the leaflets on the amount of returned flow. Furthermore, the deformation of the leaflets was measured during systole. The results were found to be consistent with the relevant literature.

Keywords: Fluid-Structure Interaction, hemodynamics, mitral, regurgitation, systole

Introduction

Mitral valve regurgitation is a condition in which the valve does not close tightly and there is an abnormal reversal of blood flow from the left ventricle to the left atrium. This increases the pressure in the left atrium and may lead to complications such as dyspnea, fatigue, orthopnea, and pulmonary edema. Mitral valve regurgitation is an important health issue. More than three millions people in the USA suffer from moderate or severe regurgitation [1]. In spite of the fact that measuring hemodynamic parameters in left ventricle and mitral valve stress patterns are significantly challenging, numerical analyses can be used to develop new models to further understand this issue [2]. Coincident with developments in non-invasive blood flow imaging (echo-doppler and Magnetic Resonance Imaging, MRI), in recent years significant studies have combined such imaging with numerical simulation [3]; with applications to human mitral valves, including prediction of disease progression and treatment.

One of the first attempts for modeling of mitral regurgitation (MR) was by Dent et al. [4] who introduced a mathematical model for the quantification of MR using experimental data. In parallel, Doppler echocardiography, color Doppler assessment, and color Doppler mapping were used to study the degree of MR [5,6,7]. More recently, Wenk et al. [8] have studied a finite element model of the left ventricle with mitral valve. Their model was based on magnetic resonance imaging data from a sheep that had developed moderate ischemic MR after postero-basal myocardial infarction. A three-dimensional (3D) FSI model of MR flow was presented by Mao et al. [9] that showed the FSI method could simulate the coupled valves structure response and the intraventricular hemodynamics in left ventricle. Little et al [10] introduced a 3D ultrasound imaging model of MR. Einstein [11] studied MR by using a Fluid-Structure Interaction (FSI) model.

1 Together these studies have presented a comprehensive strategy for analyzing MR.
2 Development by This et al. [12] presented a one-way FSI model to simulate three
3 different mitral valve defects, including blood-flow in patients. While numerical
4 techniques, including FSI, have been applied for the development of a ‘healthy’
5 mitral valve model [13-15], Su et al. [16] studied the intraventricular flow in a
6 patient-specific mitral and aortic valves integrated model including left ventricle
7 using a Two-dimensional methodology. Their results confirmed the ability of
8 estimating the patient-specific intraventricular flow by means of numerical method
9 together with FSI approach. While models of MR are developing, there has been
10 limited assessment of the effect of ventricular and annular dimensions on MR.
11 Particularly valuable is intraventricular flow during the early diastolic phase, when
12 the hemodynamic parameters including vortices may be important in filling [17],
13 closure and regurgitation of the mitral valve.

14 The aim of this study is the development of a computational model for the
15 assessment of MR, including its progression from mild to severe. To assess the
16 feasibility of developing such an FSI model, a 2D model is assessed, which may
17 also be more likely to undergo clinical translation due to the model solution times
18 [3]. This initial model has focused on assessing MR during three main cases: mild,
19 moderate, and severe conditions.

21 **Methods**

22 A 2D simplified parametric model of the mitral valve was built using Comsol
23 Multiphysics software (Figure 1). This model was based on certain dimensions of
24 left ventricle that was measured through an MRI image. The model included two
25 leaflets and a semi elliptical left ventricle. Both leaflets have the same geometry

and considered as symmetrical. The tips of the leaflets were set as touching in a 'normal' position [15] whereas the distance between the leaflets is 1 mm (mild MR), 3 mm (moderate MR), and 5 mm (severe MR) inspired from a physical model [18]. Blood is a virtually incompressible fluid and non-Newtonian [19-21]; however, it can be considered as Newtonian in large arteries and the heart. In the present study, we assumed blood to be a Newtonian fluid [22-23]. The leaflets were considered as isotropic and linear elastic material with Poisson's ratio of 0.33 [24] and Young's modulus of 1 MPa [25]. The viscosity of blood was set to 2.7 mPa.s and density of 1060 kg/m³ [17]. Because the model was solved during the systolic phase, the ventricular pressure as well as the atrial pressure were considered as inputs.

Boundary conditions

The total time of systolic phase was 0.3 s which was considered for the simulation. The fluid applied a force on the leaflets leading to closure; further described elsewhere [13]. The functions of the ventricular pressure and atrial pressure were defined in the software as time-dependent inlet boundary conditions (Figure 2a, 2b) [16]. For the systolic phase, an aortic velocity function was defined at the boundary of a simplified aorta (Figure 2c, 2d). All other boundaries, including ventricle walls were considered as a non-slip condition. It should be noted that mitral leaflets and related edges were restricted from moving.

Triangular normal elements were used, with a finer meshing was set for leaflet areas in order to get more precise numerical solution (Figure 3; Table 1). A moving Arbitrary-Lagrange-Euler (ALE) mesh was applied to the leaflets and the blood flow, however, the other areas had a fixed mesh. COMSOL Multiphysics (Comsol Multiphysics, Stockholm, Sweden) was used to solve the model using a transient FSI method; described in further detail elsewhere [26-28].

Table.1: Specifications of mesh parameters

Number of vertex elements	13
Number of boundary elements	245
Number of elements	2781
Minimum element quality	0.505

Results

The preformed numerical simulation was used to predict the pressure, velocity, and Von Mises stress contours, for blood-flow and the valve leaflets, respectively, during mild, moderate, and severe MR. The extracted hemodynamic parameters are presented and compared as below.

1-Pressure:

Figure 4a-4c provides the pressure contours in three different time steps for severe MR. In severe MR, the leaflets were not attached to each other completely and there is an approximately 5 mm distance between the leaflets. The contours showed a pressure drop in the left ventricle. At a time of 0.3 s, the ventricle pressure variation was between 0.9 to 14.5 kPa with much back flow to the atrium.

Figure 5a-5c shows the pressure contours at three different time steps for moderate MR. The pressure drop within the left ventricle was lower than for severe MR but was still between 10-15 kPa. This drop was still considerable and due to a 3 mm distance between the leaflets.

Figure 6a-6c presents the pressure contours for mild MR. The ventricular pressure reached to 16 kPa which was near to that for a 'healthy' valve. The

distance of 1 mm, between leaflets, was not effective in reducing the ventricle pressure as compared to severe MR. The backflow of blood towards the atrium was much lower than for moderate and severe MR.

Therefore, the severity of MR could be quantified from the pressure contours and decreasing of ventricle pressure. For severe MR, a decrease in ventricle pressure is predicted, down to 0.9 kPa (at 0.3 s). Furthermore, the backflow of blood was much greater toward the atrium during severe MR. Wenk et al [8] reported the left ventricle pressure between 0.8 kPa to 12.19 kPa during MR. These values are consistent with our results during moderate and severe MR, which ranged from 0.9 kPa to 14 kPa.

2-Velocity:

The velocity streamlines of severe, moderate and mild MR are shown in Figures 7-9, respectively. Moreover, Figure 10 shows the maximum velocity at the tip of the leaflets area for three time steps during systole in three MR modes. According to these results, it can be concluded that the velocity increases up to 6 and 4.8 m/s at the leaflet tips area in severe and moderate MR, respectively, resulting to the formation of a velocity jet. However, there appeared to be a slight increase in the velocity (about 1.6 m/s) for mild condition resulting no velocity jet. The velocity changing trend is generally consistent with all MR conditions including some vortices evident in the center of ventricle. Vermeulen [29] reported the range of jet velocities between 2.6 m/s to 4 m/s during mitral valve leakage. However, Lassila [30], Thomas [31], and Grayburn [32] concluded that the jet velocity is increased to the highest value during severe MR.

3- Stress:

1 The stress distribution varied significantly over the leafs in our
2 results. Stress in Severe MR case Figure 11 (a,b,c) presents the Von Mises
3 stress distribution in severe MR case in three time steps. The stress varied
4 between 100-500 kPa. Stress in Moderate and mild MR case Figure 12 (a,b)
5 shows the stress distribution in moderate and mild MR case at $t=0.3$ s. The
6 average of Von Mises stress on leaflets at mid systole (0.2 sec) for severe,
7 moderate and mild MR are 275, 214 and 74 kPa, respectively. Lee et al.
8 predicted the *in vivo* stresses of a region of interest using a numerical
9 analysis method for the anterior leaflet of a healthy mitral valve. The total
10 range of region of interest (ROI) stresses that they estimated were between
11 80.9 to 593.2 kPa, consistent with our results [33]. The stresses varied
12 between 100 to 500 kPa over the leaflets based on our numerical results for
13 moderate and severe MR. For instance, Wenk et al. [8] reported the
14 effective stress in the center of the anterior leaflet to 119 kPa. Prot et al [34]
15 results showed the leaflet stress to be 130-220 kPa. In another study, Salgo
16 [35] reported higher stresses up to 400 kPa. The difference between the
17 reported values comes back to different type of leaflet material models
18 including linear isotropic, orthotropic, etc.

20 **Discussions:**

21 In this study, an FSI model was developed to simulate the progression of
22 MR disease from mild to severe. Using this model, the blood hemodynamic
23 parameters can be extracted within the progression process and compared
24 between different intensities of MR. There are some limitations to
25 understanding the exact physiology of MV function in healthy and diseased
26 states due to the influence of elastic leaflets and the role of left ventricle in
27 fluid dynamics [36-38]. Therefore, the elastic material properties were also

1 incorporated into simulation in addition to non-Newtonian fluid properties.
2 FSI was used because of the forces that fluid had applied on the leaflets in
3 interaction with the structure which leads to large structural deformations.

4 A comparison of the results obtained between the different severities of MR has
5 led to the following findings:

- 6 • Increasing severity of disease leads to decrease of intraventricular
7 pressure.
- 8 • As the distance between the leaflets increases, the Von Mises stress
9 on the leaflets increases and the return flow to the atrium increases.
- 10 • The increased velocity near the tip of the leaflets in severe MR
11 causes the vortex in the atrium area. This vortex is due to the
12 interaction of the back flow from the ventricle to the fluid flow in the
13 atrium.
- 14 • Another developed vortex, inside the left ventricle, was increased
15 during the early to the end of the systolic phase.
- 16 • It was also shown that a pair of vortices, which were developed
17 under the leaflets, led to valve closure.

18
19 It was shown that this method can measure the stress patterns on the
20 leaflets as the disease progresses. We tried to develop a model to study the
21 hemodynamic parameters of blood flow in mitral regurgitation case. It was
22 found that the pressure throughout the ventricle is decreased and also the
23 velocity jet increased as the distance between leaflets is increased.

24 Moreover, it was shown that an increase in the distance between the leaflets
25 increases the average of Von Mises stress on leaflets at mid systole.

On the other hand, considering the same input boundary conditions for different MR states, the contraction of ventricle muscle is not effective, so the leakage plays an important role on decreasing the pressure. When the leakage occurs in one of the components, the pump will not be able to create ideal pressure. In a similar way, for severe disorder mitral function, severe leakage of blood from left ventricle to the atrium (flow back) during systole is observed and leads to decrease of the pressure in the ventricle. There are simplifications in this study, particularly around the use of a 2D model which limits assessment of mitral annular motion. In future, this may be overcome by use of a 3D model. However, in current solution times are prohibitory as regards real-time translation into clinical practice; unlike 2D models which solve over a time-frame which is compatible with clinical practice, as discussed elsewhere [39]. The model presented in this study along with the obtained results was able to capture the mitral regurgitation in different cases based on the gap size between the leaflets. It is important to consider multiple parameters for evaluating MR severity and one single measurement is not sufficient. Thus, we calculated different hemodynamic parameters of MR including pressure and velocity contours as well as leaflets' stress. These predicted results show that a regurgitant jet flow is always present in different MR cases due to an open way from left ventricle to atrium. The severity of MR was studied quantitatively as the area of the jet by above mentioned hemodynamic parameters. We believe that our model was able to demonstrate the function of MR and it can be very helpful for surgeons to use surgical plans based on predicted results of blood flow hemodynamics and leaflet stress during mitral regurgitation.

Conclusion

In this study, we have modelled the left ventricle with symmetric mitral valves integrated in 2D. In addition to the mitral valve prescribed according to progression of MR disease, the FSI approach was applied to the leaflets of valves to simulate the interaction between the blood flow and elastic leaflet. We have successfully demonstrated important parameters (such as pressure and velocity) and development in the mitral regurgitation.

Compliance with Ethical Standards

All procedures performed in studies involving human participants were in accordance with the ethical standards of the institutional and/or national research committee and with the 1964 Helsinki declaration and its later amendments or comparable ethical standards.

Funding: None.

Conflict of Interest: Authors declare that they have no conflict of interests.

References:

- [1] Athappan G, Sorajja P, Gössl M. Percutaneous Treatment of Mitral Regurgitation: Present and Future. Journal of the Minneapolis Heart Institute Foundation. 2017 Dec;1(2):113-23.
- [2] Gao H, Ma X, Qi N, Berry C, Griffith BE, Luo X. A finite strain nonlinear human mitral valve model with fluid-structure interaction. International journal for numerical methods in biomedical engineering. 2014 Dec;30(12):1597-613.
- [3] Wong KK, Wang D, Ko JK, Mazumdar J, Le TT, Ghista D. Computational medical imaging and hemodynamics framework for functional analysis and

assessment of cardiovascular structures. Biomedical engineering online. 2017 Dec;16(1):35.

[4] Dent JM, Jayaweera AR, Glasheen WP, Nolan SP, Spotnitz WD, Villanueva FS, Kaul S. A mathematical model for the quantification of mitral regurgitation. Experimental validation in the canine model using contrast echocardiography. Circulation. 1992 Aug 1;86(2):553-62.

[5] Shiota T, Jones M, Teien DE, Yamada I, Passafini A, Ge S, Shandas R, Valdes-Cruz LM, Sahn DJ. Evaluation of mitral regurgitation using a digitally determined color Doppler flow convergence'centerline'acceleration method. Studies in an animal model with quantified mitral regurgitation. Circulation. 1994 Jun 1;89(6):2879-87.

[6] Shiota T, Jones M, Teien D, Yamada I, Passafini A, Knudson O, Sahn DJ. Color Doppler regurgitant jet area for evaluating eccentric mitral regurgitation: An animal study with quantified mitral regurgitation. Journal of the American College of Cardiology. 1994 Sep 1;24(3):813-9.

[7] Stewart WJ, Currie PJ, Salcedo EE, Klein AL, Marwick T, Agler DA, Homa D, Cosgrove DM. Evaluation of mitral leaflet motion by echocardiography and jet direction by Doppler color flow mapping to determine the mechanism of mitral regurgitation. Journal of the American College of Cardiology. 1992 Nov 15;20(6):1353-61.

[8] Wenk JF, Zhang Z, Cheng G, Malhotra D, Acevedo-Bolton G, Burger M, Suzuki T, Saloner DA, Wallace AW, Guccione JM, Ratcliffe MB. First finite element model of the left ventricle with mitral valve: insights into ischemic mitral regurgitation. The Annals of thoracic surgery. 2010 May 1;89(5):1546-53.

[9] Mao W, Caballero A, McKay R, Primiano C, Sun W. Fully-coupled fluid-structure interaction simulation of the aortic and mitral valves in a realistic 3D left ventricle model. PloS one. 2017 Sep 8;12(9):e0184729.

[10] Little SH, Igo SR, McCulloch M, Hartley CJ, Nosé Y, Zoghbi WA. Three-dimensional ultrasound imaging model of mitral valve regurgitation: design and evaluation. Ultrasound in medicine & biology. 2008 Apr 1;34(4):647-54.

[11] Einstein DR, Del Pin F, Jiao X, Kuprat AP, Carson JP, Kunzelman KS, Cochran RP, Guccione JM, Ratcliffe MB. Fluid–structure interactions of the mitral valve and left heart: comprehensive strategies, past, present and future.

1 International Journal for Numerical Methods in Biomedical Engineering. 2010
2 Mar;26(3-4):348-80.

3 [12] This A, Morales HG , and Bonnefous O. Proximal Isovelocity Surface For
4 Different Mitral Valve Hole Geometries. VII European Congress on
5 Computational Methods in Applied Sciences and Engineering ECCOMAS
6 Congress 2016. DOI:10.7712/100016.1800.6456

7 [13] Espino DM, Shepherd DE, Hukins DW. Evaluation of a transient,
8 simultaneous, arbitrary Lagrange–Euler based multi-physics method for simulating
9 the mitral heart valve. Computer methods in biomechanics and biomedical
10 engineering. 2014 Mar 12;17(4):450-8.

11 [14] Gao H, Feng L, Qi N, Berry C, Griffith BE, Luo X. A coupled mitral valve—
12 left ventricle model with fluid–structure interaction. Medical engineering &
13 physics. 2017 Sep 1;47:128-36.

14 [15] Thomas L, Foster E, Schiller NB. Peak mitral inflow velocity predicts mitral
15 regurgitation severity. Journal of the American College of Cardiology. 1998 Jan
16 1;31(1):174-9.

17 [16] Su B, Zhong L, Wang XK, Zhang JM, San Tan R, Allen JC, Tan SK, Kim S,
18 Leo HL. Numerical simulation of patient-specific left ventricular model with both
19 mitral and aortic valves by FSI approach. Computer methods and programs in
20 biomedicine. 2014 Feb 1;113(2):474-82.

21 [17] AL-ATABI M, Espino DM, Hukins DW. Computer and experimental
22 modelling of blood flow through the mitral valve of the heart. Journal of
23 Biomechanical Science and Engineering. 2010;5(1):78-84.

24 [18] Espino DM, Shepherd DE, Buchan KG. Effect of mitral valve geometry on
25 valve competence. Heart and vessels. 2007 Mar 1;22(2):109-15.

26 [19] Amlimohamadi H, Akram M, Sadeghy K. Flow of a Casson fluid through a
27 locally-constricted porous channel: a numerical study. Korea-Australia Rheology
28 Journal. 2016 May 1;28(2):129-37.

29 [20] Alimohamadi H, Sadeghy K. On the use of magnetic fields for controlling the
30 temperature of hot spots on porous plaques in stenosis arteries. 日本レオロジー学
31 会誌. 2016 Jan 15;43(5):135-44.

- 1 [21] Jamalabadi MY, Daqiqshirazi M, Nasiri H, Safaei MR, Nguyen TK. Modeling
2 and analysis of biomagnetic blood Carreau fluid flow through a stenosis artery
3 with magnetic heat transfer: A transient study. PloS one. 2018 Feb
4 28;13(2):e0192138.
- 5 [22] Ma X, Gao H, Griffith BE, Berry C, Luo X. Image-based fluid–structure
6 interaction model of the human mitral valve. Computers & Fluids. 2013 Jan
7 30;71:417-25.
- 8 [23] Carty G, Chatpun S, Espino DM. Modeling blood flow through intracranial
9 aneurysms: A comparison of Newtonian and non-Newtonian viscosity. Journal of
10 Medical and Biological Engineering. 2016 Jun 1;36(3):396-409.
- 11 [24] Espino DM, Shepherd DE, Hukins DW. Development of a transient large
12 strain contact method for biological heart valve simulations. Computer methods in
13 biomechanics and biomedical engineering. 2013 Apr 1;16(4):413-24.
- 14 [25] Lim KH, Yeo JH, Duran CM. Three-dimensional asymmetrical modeling of
15 the mitral valve: a finite element study with dynamic boundaries. J Heart Valve
16 Dis. 2005 May 1;14(3):386-92.
- 17 [26] Marom G. Numerical methods for fluid–structure interaction models of aortic
18 valves. Archives of Computational Methods in Engineering. 2015 Nov
19 1;22(4):595-620.
- 20 [27] Kuan MY, Espino DM. Systolic fluid–structure interaction model of the
21 congenitally bicuspid aortic valve: assessment of modelling requirements.
22 Computer methods in biomechanics and biomedical engineering. 2015 Sep
23 10;18(12):1305-20.
- 24 [28] Espino DM, Shepherd DE, Hukins DW. Transient large strain contact
25 modelling: A comparison of contact techniques for simultaneous fluid–structure
26 interaction. European Journal of Mechanics-B/Fluids. 2015 May 1;51:54-60.
- 27 [29] Vermeulen M, Van Der Smissen B, Claessens T, Kaminsky R, Segers P,
28 Verdonck P, Van Ransbeeck P. Mitral valve leakage quantification by means of
29 experimental and numerical flow modeling. Acta Mechanica Slovaca. 2010 Jun
30 1;14(2):18-25.
- 31 [30] Lassila T, Malossi C, Stevanella M, Votta E, Redaelli A, Deparis S.
32 Simulation of left ventricle fluid dynamics with mitral regurgitation from magnetic

1 resonance images with fictitious elastic structure regularization. arXiv preprint
2 arXiv:1707.03998. 2017 Jul 13.

3 [31] Thomas L, Foster E, Hoffman JI, Schiller NB. The mitral regurgitation index:
4 an echocardiographic guide to severity. *Journal of the American College of*
5 *Cardiology*. 1999 Jun 1;33(7):2016-22.

6 [32] Grayburn PA. How to measure severity of mitral regurgitation. *Postgraduate*
7 *medical journal*. 2008 Aug 1;84(994):395-402. doi:10.1136/hrt.2005.086462.

8 [33] Lee CH, Amini R, Gorman RC, Gorman III JH, Sacks MS. An inverse
9 modeling approach for stress estimation in mitral valve anterior leaflet
10 valvuloplasty for in-vivo valvular biomaterial assessment. *Journal of*
11 *biomechanics*. 2014 Jun 27;47(9):2055-63.

12 [34] Prot V, Skallerud B, Sommer G, Holzapfel GA. On modelling and analysis of
13 healthy and pathological human mitral valves: two case studies. *Journal of the*
14 *mechanical behavior of biomedical materials*. 2010 Feb 1;3(2):167-77.

15 [35] Salgo IS, Gorman III JH, Gorman RC, Jackson BM, Bowen FW, Plappert T,
16 St John Sutton MG, Edmunds Jr LH. Effect of annular shape on leaflet curvature in
17 reducing mitral leaflet stress. *Circulation*. 2002 Aug 6;106(6):711-7.

18 [36] Baxter J, Buchan KG, Espino DM. Viscoelastic properties of mitral valve
19 leaflets: An analysis of regional variation and frequency-dependency. *Proceedings*
20 *of the Institution of Mechanical Engineers, Part H: Journal of Engineering in*
21 *Medicine*. 2017 Oct;231(10):938-44.

22 [37] Toma M, Jensen MØ, Einstein DR, Yoganathan AP, Cochran RP, Kunzelman
23 KS. Fluid–structure interaction analysis of papillary muscle forces using a
24 comprehensive mitral valve model with 3D chordal structure. *Annals of*
25 *biomedical engineering*. 2016 Apr 1;44(4):942-53.

26 [38] Dahl SK, Vierendeels J, Degroote J, Annerel S, Hellevik LR, Skallerud B. FSI
27 simulation of asymmetric mitral valve dynamics during diastolic filling. *Computer*
28 *methods in biomechanics and biomedical engineering*. 2012 Feb 1;15(2):121-30.

29 [39] Bahraseman HG, Hassani K, Navidbakhsh M, Espino DM, Sani ZA,
30 Fatourae N. Effect of exercise on blood flow through the aortic valve: a combined
31 clinical and numerical study. *Computer methods in biomechanics and biomedical*
32 *engineering*. 2014 Dec 10;17(16):1821-34.